# CEMHER



# SAFETY DATA SHEET

CEMHER MICROTADELAKT LIME BASE PLASTER



# SAFETY DATA SHEET MORTAR CEMHER

According to Annex II to REACH - Regulation 2020/878

Product: MICROTADELAKT

Version 2.0 / 29.12.2023

Replaces all previous versions

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Product name: MICROTADELAKT

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

#### Intended use:

Mass colored plaster

Product to be mixed with water for application on buildings.

Product for craft and private use.

Any other use is not recommended.

#### 1.3 Details of the supplier of the safety data sheet

Company: PINTURAS KILNHER

Address: Pol. Ind. La Figuera, C/LLanterners, 44. 46394

City: ALACUAS Province: VALENCIA

Telephone: (+34) 961 505 024 Fax: (+34) 961 505 024 E-mail: kilnher@kilnher.com Web: www.kilnher.com

#### 1.4 Emergency telephone number

(+34) 961 505 024 (Only available during office hours; Monday-Friday; 07:00-15:00)

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Version 2.0 / 29.12.2023 Replaces all previous versions

Hazard class	Hazard category	Indications of danger	Indication
Serious eye damage	1	H318	Causes serious eye damage
Skin irritation	2	H315	Causes skin irritation
Specific target organ toxicity - single exposure	3	H335	May cause respiratory irritation
Skin sensitization	1	H317	May cause an allergic skin reaction

#### 2.2 Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

#### **Hazard pictograms**

GHS05



# Signal word

Danger

#### **Hazard statements**

**H318** Causes serious eye damage.

H315 Causes skin irritation.

H335 May cause respiratory irritation.

H317 May cause an allergic skin reaction.

GHS07



#### **Precautionary statements**

**P101** If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P261 Avoid breathing dust.

**P280** Wear protective gloves / face protection.

**P302+P352** IF ON SKIN: Wash with plenty of of soap and water.

**P304+P340** IF INHALED: Remove person to fresh air and keep comfortable for breathing.

**P305+P351+P338** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

**P310** Immediately call a POISON CENTER / doctor / . . . **P403+P233** Store in a well-ventilated place. Keep container tightly closed.

Contains: WHITE CEMENT NATURAL HYDRAULIC LIME NHL HYDRATED LIME

#### 2.3 Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration ≥ 0.1%.

The mixture has a low chromate content. After adding water the soluble chromium (VI) content is at most 2 ppm on the dry product.

To maintain a low chromate content, store it properly, in dry conditions, respecting the maximum expected storage terms.

The percentage of respirable crystalline silicon oxide is less than 1%. Therefore the product is not subject to identification. However it is advisable to use respiratory protection.

### **SECTION 3: Composition/information on ingredients**

#### 3.1 Substances

Not applicable

#### 3.2 Mixtures

Name	Product identifier	%	Classification according to Regula- tion (EC) No. 1272/2008 [CLP]
HYDRATED LIME	INDEX: - EC: 215-137-3 CAS: 1305-62-0	10 ≤ x < 25	Eye Dam. 1 H318 Skin Irrit. 2 H315 STOT SE 3 H335
NATURAL HYDRAULIC LIME NHL	INDEX: - EC: 285-561-1 CAS: 85117-09-5	10 ≤ x < 25	Eye Dam. 1 H318 Skin Irrit. 2 H315 STOT SE 3 H335
WHITE CEMENT	INDEX: - EC: 266-043-4 CAS: 65997-15-1	1≤x <3	Eye Dam. 1 H318 Skin Irrit. 2 H315 STOT SE 3 H335 Skin Sens. 1B H317

<sup>\*</sup>The full wording of hazard (H) phrases is given in section 16 of the sheet.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

### Eyes

Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

#### Skin

Remove contaminated clothing. Rinse skin with a shower immediately. Wash contaminated clothing before using it again.

#### Inhalation

Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

#### Ingestion

Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

# 4.2 Most important symptoms and effects, both acute and delayed Potential acute health effects

Specific information on symptoms and effects caused by the product are unknown.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Information not available

# **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

#### SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

# 5.2 Special hazards arising from the substance or mixture

# HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products. The product is combustible and, when the powder is released into the air in sufficient concentrations and in the presence of a source of ignition, it can create explosive mixtures with air. Fires may start or get worse by leakage of the solid product from the container, when it reaches high temperatures or through contact with sources of ignition.

#### 5.3 Advice for firefighters

#### **GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

Version 2.0 / 29.12.2023

Replaces all previous versions

# SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

#### **SECTION 6: Accidental release measures**

# 6.1 Personal precautions, protective equipment and emergency procedures

If there are no contraindications, spray powder with water to prevent the formation of dust.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

#### 6.2 Environment related measures

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

# 6.3 Methods and material for containment and cleaning up

Collect the leaked product and place it in containers for recovery or disposal. If there are no contraindications, use jets of water to eliminate product residues.

Make sure the leakage site is well aired. Evaluate the compatibility of the container to be used, by checking section 10. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 6.4 Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

## 7.1 Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

# 7.2 Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

# 7.3 Specific end use(s)

Information not available.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

Regulatory parameters						
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS				
HRV	Hrvatska	Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnimkemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)				
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)				
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.				
	TLV-ACGIH	ACGIH 2021				

#### **HYDRATED LIME**

Threshold Limit Value						
Typo	Country	TWA/8h		STEL/	STEL/15min	
Туре	Country	mg/m3	ppm	mg/m3	ppm	Observations
VLEP	FRA	5				
GVI/KGVI	HRV	5				
WEL	GBR	5				
OEL	EU	5				
TLV-ACGIH		5				

Predicted no-effect concentration - PNEC						
Normal value in fresh water	0,49	mg/l				
Normal value in marine water	0,32	mg/l				
Normal value for water, intermittent release	0,49	mg/l				
Normal value of STP microorganisms	3	mg/l				
Normal value for the terrestrial compartment	1080	mg/kg/d				

Health - Derived no-effect level - DNEL / DMEL								
Route of	Effects on consumers					Remarks / C	bservations	
exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation	4 mg/m3		1mg/m3			4 mg/m3	1mg/m3	

# NATURAL HYDRAULIC LIME NHL

Threshold Limit Value						
Typo			TWA/8h STEL/		15min	Remarks /
Туре	Country	mg/m3	ppm	mg/m3	ppm	Observations
OEL	EU	1		4		RESP

Predicted no-effect concentration - PNEC						
Normal value in fresh water	0,574	mg/l				
Normal value in marine water	0,374	mg/l				
Normal value for fresh water sediment	1262,3	mg/kg				
Normal value for marine water, intermittent release	0,574	mg/l				
Normal value for fresh water, intermittent release	0,374	mg/l				
Normal value of STP microorganisms	3,511	mg/l				

# WHITE CEMENT

Threshold Limit Value						
Typo	Country	TW	4/8h	STEL/	15min	Remarks /
Туре	Country	mg/m3	ppm	mg/m3	ppm	Observations
TLV-ACGIH		1				RESP

Predicted no-effect concentration - PNEC					
Normal value in fresh water	NEA				
Normal value in marine water	NEA				
Normal value for fresh water sediment	NEA				
Normal value for marine water sediment	NEA				
Normal value for fresh water, intermittent release	NEA				
Normal value for the terrestrial compartment	NEA				

Health - Derived no-effect level - DNEL / DMEL								
Route of	Effects on consumers			Remarks / Observations				
exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral					NEA	NEA	NEA	NEA
Inhalation					1 mg/m3		1 mg/m3	
Skin					NEA	NEA	NEA	NEA

LEGEND:

(C) = CEILING

INHAL = Inhalable Fraction RESP = Respirable Fraction THORA = Thoracic Fraction

VND = hazard identified but no DNEL/PNEC available

NEA = no exposure expected NPI = no hazard identified LOW = low hazard MED = medium hazard

HIGH = high hazard.

During the risk assessment process, it is essential to take into consideration the ACGIH occupational exposure levels for inert particulate not otherwise classified (PNOC respirable fraction: 3 mg/m3; PNOC inhalable fraction: 10 mg/m3). For values above these limits, use a P type filter, whose class (1, 2 or 3) must be chosen according to the outcome of risk assessment.

#### 8.2 Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

#### HAND PROTECTION

In the case of prolonged contact with the product, protect the hands with penetration-resistant work gloves (see standard EN 374).

Work glove material must be chosen according to the use process and the products that may form. Latex gloves may cause sensitivity reactions.

#### **SKIN PROTECTION**

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

#### **EYE PROTECTION**

Wear airtight protective goggles (see standard EN 166).

#### **RESPIRATORY PROTECTION**

Use a type P filtering facemask, whose class (1, 2 or 3) and effective need, must be defined according to the outcome of risk assessment (see standard EN 149).

### **ENVIRONMENTAL EXPOSURE CONTROLS**

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

# **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

Appearance: powder

Colour: as showed in color folder

Odour: odourless

Melting point / freezing point: not available

Initial boiling point: not applicable

Flammability: not available

Lower explosive limit: not available Upper explosive limit: not available

Flash point: not applicable

Auto-ignition temperature: not available

**Decomposition temperature:** not available

**pH**: 12

Kinematic viscosity: not available

Solubility: not available

Partition coefficient: n-octanol/water: not available

Vapour pressure: not available

Density and/or relative density: 1,3

Relative vapour density: not available

Particle characteristics: not available

#### 9.2 Other information

#### 9.2.1 Information with regard to physical hazard classes

Information not available

#### 9.2.2 Other safety characteristics

Granulometry: 1.2 mm

#### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

#### HYDRATED LIME

Stable in normal conditions of use and storage.

#### WHITE CEMENT

When mixed with water, it hardens to form a stable mass

#### 10.2 Chemical stability

The product is stable in normal conditions of use and storage.

#### **HYDRATED LIME**

Stable in normal conditions of use and storage.

# 10.3 Possibility of hazardous reactions

The powders are potentially explosive when mixed with air.

#### **HYDRATED LIME**

Develops hydrogen on contact with: aluminium,brass,moisture. Reacts with: carbon dioxide.

# NATURAL HYDRAULIC LIME NHL

It reacts exothermically with acids.

#### 10.4 Conditions to avoid

Avoid environmental dust build-up.

#### **HYDRATED LIME**

Decomposes if exposed to: moisture, moist air.

#### NATURAL HYDRAULIC LIME NHL

Decomposes when exposed to air and moisture.

#### 10.5 Incompatible materials

#### **HYDRATED LIME**

Avoid contact with: acids.

#### **NATURAL HYDRAULIC LIME NHL**

Aluminum and brass.

#### WHITE CEMENT

Incompatible with acids, ammonium salts, aluminum, alkaline metals and alkaline earth metals.

#### 10.6 Hazardous decomposition products

#### **HYDRATED LIME**

Develops hydrogen on contact with: aluminium,brass,moisture.

# NATURAL HYDRAULIC LIME NHL

Reacts with aluminum and brass, releasing hydrogen.

#### WHITE CEMENT

Develops hydrogen in contact with aluminum powder.

## **SECTION 11: Toxicological information**

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and

other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

#### 11.1.1 Acute toxicity

ATE (Inhalation) of the mixture	Not classified (no significant component)
ATE (Oral) of the mixture:	Not classified (no significant component)
ATE (Dermal) of the mixture:	Not classified (no significant component)

HYDRATED LIME		
LD50 (Dermal)	> 2500 mg/kg	
LD50 (Oral)	> 2000 mg/kg	

NATURAL HYDRAULIC LIME NHL			
LD50 (Dermal)	> 2500 mg/kg rabbit		
LD50 (Oral)	> 2000 mg/kg rat		
LC50 (Inhalation mists/powders)	6, 04 mg/l/4h		

#### 11.1.2 Skin corrosion/irritation

Causes skin irritation

### 11.1.3 Serious eye damage/irritation

Information not available

### **SECTION 12: Ecological information**

#### 12.1 Toxicity

Information not available

#### 12.2 Persistence and degradability

Information not available

#### 12.3 Bioaccumulative potential

Information not available

#### 12.4 Mobility in soil

Information not available

#### 12.5 Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

# 12.6 Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

### 12.7 Other adverse effects

Information not available

#### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

#### **CONTAMINATED PACKAGING**

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

# **SECTION 14: Transport information**

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

#### 14.1 UN number or ID number

Not applicable

#### 14.2 UN proper shipping name

Not applicable

#### 14.3 Transport hazard class(es)

Not applicable

#### 14.4 Packing group

Not applicable

#### 14.5 Environmental hazards

Not applicable

#### 14.6 Special precautions for user

Not applicable

# 14.7 Maritime transport in bulk according to IMO instruments

Information not relevant

# **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006 Contained substance: Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors: not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.

Substances subject to authorisation (Annex XIV REACH): None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012: None

Substances subject to the Rotterdam Convention: None

Substances subject to the Stockholm Convention: None

#### **Healthcare controls**

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

#### 15.2 Chemical Safety Assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

#### **SECTION 16: Other information**

#### 16.1 Text of hazard (H) indications mentioned in section 2-3 of the sheet

Eye Dam. 1 Serious eye damage, category 1

Skin Irrit. 2 Skin irritation, category 2

STOT SE 3 Specific target organ toxicity - single exposure, category 3

Skin Sens. 1 Skin sensitization, category 1

Skin Sens. 1B Skin sensitization, category 1B

**H318** Causes serious eye damage.

H315 Causes skin irritation.

H335 May cause respiratory irritation.

H317 May cause an allergic skin reaction.

### 16.2 Use descriptor system

AC	4	Stone, plaster, cement, glass and ceramic articles
ERC	10a	Widespread use of articles with low release (outdoor)
ERC	11a	Widespread use of articles with low release (indoor)
PC	9b	Fillers, putties, plasters, modelling clay
PROC	11	Non industrial spraying
PROC	19	Manual activities involving hand contact
SU	19	Building and construction work

#### 16.3 Legend

ADR: European Agreement concerning the carriage of

Dangerous goods by Road **ATE:** Acute Toxicity Estimate

**CAS:** Chemical Abstract Service Number

 $\textbf{CE50:} \ \textbf{Effective concentration (required to induce a 50\%)}$ 

effect)

CE: Identifier in ESIS (European archive of existing subs-

tances)

CLP: Regulation (EC) 1272/2008

DNEL: Derived No Effect Level

EmS: Emergency Schedule

GHS: Globally Harmonized System of classification and

labeling of chemicals

IATA DGR: International Air Transport Association Dange-

rous Goods Regulation

IC50: Immobilization Concentration 50%

**IMDG:** International Maritime Code for dangerous goods

IMO: International Maritime Organization INDEX: Identifier in Annex VI of CLP LC50: Lethal Concentration 50%

LD50: Lethal dose 50%

**OEL:** Occupational Exposure Level

PBT: Persistent bioaccumulative and toxic as REACH

Regulation

**PEC:** Predicted environmental Concentration

PEL: Predicted exposure level

**PNEC:** Predicted no effect concentration **REACH:** Regulation (EC) 1907/2006

RID: Regulation concerning the international transport of

dangerous goods by train **TLV:** Threshold Limit Value

TLV CEILING: Concentration that should not be exceeded

during any time of occupational exposure.

**TWA:** Time-weighted average exposure limit

**TWA STEL:** Short-term exposure limit **VOC:** Volatile organic Compounds

vPvB: Very Persistent and very Bioaccumulative as for

**REACH Regulation** 

WGK: Water hazard classes (German) .

#### 16.4 General Bibliography

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4 . Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5 . Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6 . Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7 . Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8 . Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9 . Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10 . Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)

The Merck Index. - 10th Edition

Handling Chemical Safety

INRS - Fiche Toxicologique (toxicological sheet)

Patty - Industrial Hygiene and Toxicology

N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition

IFA GESTIS website

ECHA website

Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

### 16.5 Note for users

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses. Provide appointed staff with adequate training on how to use chemical products.

#### 16.6 Calculation methods for classification

**Chemical and physical hazards:** Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

**Health hazards:** Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

**Environmental hazards:** Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.